

FEATURES AND BENEFITS

- Exceptional fidelity and surprising power capability delivered in a compact, light enclosure
- Extraordinarily flat amplitude and phase response ensures tonal accuracy and precise imaging
- Wide (ULTRA-X40) or Controlled (ULTRA-X42) pattern
- Rotatable horn provides installation flexibility
- Integral stand mount and QuickFly® mounting options facilitate rigging

APPLICATIONS

- Stadiums and theme parks
- Concert halls and houses of worship
- Theatrical sound reinforcement
- Portable and installed audio-visual systems
- Nightclubs
- Compact voice reinforcement systems

ACCESSORIES AND ASSOCIATED PRODUCTS

MCP50-X40 Cluster Plate: The MCP50-X40 50 Degree Cluster Plate kit includes two cluster plates to facilitate installation of ULTRA-X40/42 loudspeakers in both horizontal and vertical clusters at angles between 10 and 50 degrees in 5 degree increments. The kit includes eight M8 bolts and eight M8 knobs. The MTC-X40 Top Channel accessory (sold separately) can be attached to the MCP50-X40 as a top pick up point.

MCP70-X40 Cluster Plate: The MCP70-X40 70 Degree Cluster Plate kit includes two cluster plates to facilitate installation of ULTRA-X40/42 loudspeakers in both horizontal and vertical clusters at angles between 40 and 70 degrees in 5 degree increments. The kit includes eight M8 bolts and eight M8 knobs. The MTC-X40 Top Channel accessory (sold separately) can be attached to the MCP70-X40 as a top pick up point.

MPK-POLE 35MM/M20 Adjustable Pole Mount: Adjustable length 927–1524 mm (36.5–60 in) pole with assisted lift. Lower shaft fits 35 mm cups or use the removable M20 threaded lug for added stability. Upper shaft includes a PAS-M20 Adapter Sleeve to fit loudspeakers with 35 mm and M20 internal pole mounts onto a 35 mm speaker stand. (Can also buy the PAS-M20 Adapter Sleeve separately). Additional 35 mm to 38 mm (1.5 in) adapter and PAS-M8 Adapter Sleeve included.

MTB-X40 Top Bracket: The MTB-X40 Top Bracket kit includes a heavy-duty, U-bracket style accessory that facilitates mounting of ULTRA-X40/42 loudspeakers from the ceiling or a truss using the cluster plates. The design supports 5–25 degrees of downtilt and 5 degrees of uptilt. In addition, the MTB-X40 Top Bracket enables mounting of a single ULTRA-X40/42 onto the floor for front-fills. The kit includes four M8 bolts and four M8 knobs.

35MM Pole Stand Adapter: This large base stand adapter can be used to mount the MTB-X40 Top Bracket or the MUB-X40 U-bracket onto a pole.


MTC-X40 Top Channel: The MTC-X40 Top Channel kit includes a pinnable link in a channel that mounts directly to the top of the ULTRA-X40/42 rig nuts or into an MCP50-X40 or MCP70-X40 plate and supports pick-up of up to three ULTRA-X40/42 loudspeakers from a single point using the two included lock pins and 3/8-inch shackle. Using the MTC-X40 Top Channel at the bottom of the ULTRA-X40/42 to pick up multiple loudspeakers requires the use of a Thread Reducer M20 to M8 (35MM), which is not included.

MUB-X40 U-Bracket: The MUB-X40 U-Bracket allows a single ULTRA-X40/42 loudspeaker to be mounted to a wall (in either vertical or horizontal orientations), to the ceiling or onto the floor. The kit includes two M8 bolts, two M8 knobs, and a Thread Reducer M20 to M8 (35 MM) to convert the cabinet's built-in pole mount internal threads to M8 size. The MUB-X40 U-Bracket can also mount an ULTRA-X40/42 to a pole horizontally using the optional 35MM Pole Stand Adapter.


MYA-X40 Mounting Yoke: The MYA-X40 Yoke suspends a single ULTRA-X40/42 loudspeaker and supports a wide range of horizontal and vertical adjustments. The yoke attaches to the top of the loudspeaker using three rig nuts. The kit includes three M8 bolts and three M8 knobs. The yoke may also be mounted on a 35 mm pole using the optional MSA-STAND Adapter Cup 35MM accessory to facilitate easy panning and tilting.

MSA-STAND Adapter Cup 35MM: This compact cup-type adapter can be used to mount the MYA-X40 Mounting Yoke on a pole to allow for easy panning and tilting of the ULTRA-X40/42.


Thread Reducer M20 to M8 (35 mm): The Thread Reducer kit includes a 35 mm diameter, M20 to M8 thread size adapter to convert the cabinet's built-in pole mount internal threads to M8 size. It is necessary for installing the MUB-X40 U-Bracket (one is included in the MUB-X40 U-Bracket kit) and when installing the MTC-X40 Top Channel or eye bolts at the bottom of a cabinet (not included in the eye bolts or MTC-X40 Top Channel kits).




MCP50-X40 Cluster Plate




MCP70-X40 Cluster Plate




MPK-POLE 35MM/M20 Pole Kit
(PAS-M20 and PAS-M8 Adapter
Sleeves and 38 mm (1.5 in)
adapter included)




MTB-X40 Top Bracket



MTC-X40 Top Channel



MUB-X40 U-Bracket and included
Thread Reducer M20 to M8
(35 mm) shown with optional
35MM Pole Stand Adapter



MYA-X40 Yoke and optional
MSA-STAND Adapter Cup 35MM



Thread Reducer M20 to M8
(35 mm)

SPECIFICATIONS

| ACOUSTICAL ¹ | | ULTRA-X40 | ULTRA-X42 |
|--|--|--|--|
| Operating Frequency Range ² | | 55 Hz – 19.5 kHz | 55 Hz – 19.5 kHz |
| Frequency Response ³ | | 56 Hz – 19 kHz ± 4 dB | 58 Hz – 18 kHz ± 4 dB |
| Phase Response | | 90 Hz – 19.5 kHz ±45° | 90 Hz – 19.5 kHz ±45° |
| Maximum SPL ⁴ | | 138 dB | 140 dB |
| Linear Peak SPL ⁵ | | 132.5 dB with 18 dB crest factor (M-noise), 130 dB (Pink Noise), 131 dB (B-noise) | 134 dB with 18.5 dB crest factor (M-noise), 132 dB (Pink Noise), 134 dB (B-noise) |
| COVERAGE | | | |
| | | Rotatable horn: 110° x 50° | Rotatable horn: 70° x 50° |
| TRANSDUCERS | | | |
| Low Frequency | | Two 8-inch cone drivers; 4 Ω nominal impedance | |
| High Frequency | | One 3-inch diaphragm compression driver connected to a rotatable horn; 8 Ω nominal impedance | |
| AUDIO INPUT | | | |
| Type | | Differential, electronically balanced | |
| Maximum Common Mode Range | | ±15 V DC, clamped to earth for voltage transient protection | |
| Connectors | | XLR 3-pin female input with male loop output; optional XLR 5-pin connector to accommodate both balanced audio and RMS signals. | |
| Input Impedance | | 10 kΩ differential between pins 2 and 3 | |
| Wiring ⁶ | | Pin 1: Chassis/earth through 1 kΩ, 1000 pF, 15 V clamp network to provide virtual ground lift at audio frequencies Pin 2: Signal + Pin 3: Signal – Pin 4: RMS (polarity insensitive) Pin 5: RMS (polarity insensitive) Case: Earth ground and chassis | |
| Nominal Input Sensitivity | | 0 dBV (1.0 V rms) continuous is typically the onset of limiting for noise and music | |
| Input Level | | Audio source must be capable of producing of +20 dBV (10 V rms) into 600 Ω to produce the maximum peak SPL over the operating bandwidth of the loudspeaker. | |
| AMPLIFIER | | | |
| Type | | three-channel, Class-D | |
| Total Output Power ⁷ | | 1950 W peak | |
| THD, IM, TIM | | <0.02% | |
| Cooling | | Convection | |
| AC POWER | | | |
| Connector | | powerCON 20 input with loop output | |
| Automatic Voltage Selection | | 90–265 V AC, 50–60 Hz | |
| Safety Rated Voltage Range | | 100–240 V AC, 50–60 Hz | |
| Turn-on and Turn-off Points | | 90 V AC turn-on, no turn-off; internal fuse protection above 265 V AC | |
| CURRENT DRAW | | | |
| Idle Current | | 0.27 A rms (115 V AC); 0.25 A rms (230 V AC); 0.29 A rms (100 V AC) | |
| Maximum Long-Term Continuous Current (>10 sec) | | 1.9 A rms (115 V AC); 1.0 A rms (230 V AC); 2.2 A rms (100 V AC) | |
| Burst Current (<1 sec) ⁸ | | 3.1 A rms (115 V AC); 1.5 A rms (230 V AC); 3.4 A rms (100 V AC) | |
| Maximum Instantaneous Peak Current | | 6.9 A peak (115 V AC); 3.4 A peak (230 V AC); 7.9 A peak (100 V AC) | |
| Inrush Current | | <20 A peak | |

SPECIFICATIONS, CONT'D.

| RMS NETWORK (OPTIONAL) | |
|------------------------|---|
| | Two-conductor twisted-pair network that reports all operating parameters of amplifiers to system operator's host computer. |
| PHYSICAL | |
| Dimensions | W: 12.51 in (318 mm) x H: 22.31 in (567 mm) x D: 14 in (356 mm); D with handles: 15.38 in (391 mm) |
| Weight | 52 lb (23.6 kg) |
| Enclosure | Premium multi-ply birch with slightly textured black finish |
| Protective Grille | Powder-coated, round-perforated steel |
| Rigging | 11 integrated M8 threaded points; 35 mm Pole Mount with M20 thread; optional accessories for various rigging options (see accessories section). |

NOTES

- Loudspeaker system predictions for coverage and SPL are available in Meyer Sound's MAPP System Design Tool.
- Recommended maximum operating frequency range. Response depends on loading conditions and room acoustics.
- Free-field, measured with 1/3 octave frequency resolution at 4 m.
- Maximum SPL** is the peak measured in free-field at 4 m referred to 1 m using noise.
- Linear Peak SPL** is measured in free-field at 4 m referred to 1 m. Loudspeaker SPL compression measured with M-noise at the onset of limiting, 2-hour duration, and 50-degree C ambient temperature is < 2 dB.

M-noise is a full bandwidth (10 Hz–22.5 kHz) test signal developed by Meyer Sound to better measure the loudspeaker's music performance. It has a constant instantaneous peak level in octave bands, a crest factor that increases with frequency, and a full bandwidth Peak to RMS ratio of 18 dB.

Pinknoise is a full bandwidth test signal with Peak to RMS ratio of 12.5 dB.

B-noise is a Meyer Sound test signal used to ensure measurements reflect system behavior when reproducing the most common input spectrum, and to verify there is still headroom over pink noise.

- Pins 4 and 5 (RMS) only included with XLR 5-pin connector that accommodates both balanced audio and RMS signals.
- Peak power based on the maximum unclipped peak voltage the amplifier will produce into the nominal load impedance.
- AC power cabling must be of sufficient gauge so that under burst current rms conditions, cable transmission losses do not cause the loudspeaker's voltage to drop below the specified operating range.

ARCHITECTURAL SPECIFICATIONS

The loudspeaker shall be a self-powered, full-range system. The transducers shall consist of two 8-inch cone drivers and one 3-inch diaphragm compression driver connected to rotatable horns with 2 models. The wide coverage model shall have a 110° x 50° horn and the controlled coverage model shall have a 70° x 50° horn

The loudspeaker system shall incorporate internal processing electronics and a three-channel, class D amplifier. Processing functions shall include equalization, phase correction, signal division and protection for the high and low-frequency sections. Peak output power shall be 1950 W total with 8 Ω nominal impedance for the high-frequency channel and 4 Ω nominal impedance for the low-frequency channels. Distortion (THD, IM, TIM) shall not exceed 0.02%.

Performance specifications for a typical production unit shall be as follows: operating frequency range shall be 55 Hz – 19.5 kHz; phase response shall be 90 Hz – 19.5 kHz ±45°. Maximum SPL shall be 138 dB for the ULTRA-X40 and 140 dB for the ULTRA-X42, measured in free-field at 4 m referred to 1 m using noise. Linear peak SPL for the wide coverage version shall be 132.5 dB with 18 dB crest factor, measured with M-noise, free-field at 4 m referred to 1 m, and its coverage pattern (–6 dB points) shall be 110° by 50°, horizontal or vertical dependent on horn orientation. Linear peak SPL for the controlled coverage version shall be 134 dB with 18.5 dB crest factor, measured with M-noise, free-field at 4 m referred to 1 m, and its coverage pattern (–6 dB points) shall be 70° by 50°, horizontal or vertical

dependent on horn orientation.

The audio input shall be electronically balanced with a 10 kΩ impedance and shall accept a nominal 0 dBV (1 V rms) signal. The connector shall be a XLR 3-pin female with male loop.

The internal power supply shall perform automatic voltage selection, EMI filtering, soft current turn-on and surge suppression. Powering requirements shall be nominal 100, 115 or 230 V AC line current at 50 or 60 Hz. UL and CE operating voltage range shall be 100–240 V AC. Maximum peak current draw during burst shall be 3.1 A rms (115 V AC), 1.5 A rms (230 V AC), and 3.4 A rms (100 V AC). Current inrush during soft turn-on shall not exceed 20 A at 115 V AC. The AC power connector shall be powerCON.

The loudspeaker system shall provide facilities for installing Meyer Sound's optional RMS remote monitoring system.

All loudspeaker components shall be mounted in an acoustically vented trapezoidal enclosure constructed of premium multi-ply birch with a slightly textured black finish. The front protective grille shall be powder-coated, round-perforated steel. Dimensions shall be W: 12.51 in (318 mm) x H: 22.31 in (567 mm) x D: 14 in (356 mm) or 15.38 in (391 mm) with handles.

Weight shall be 52 lb (23.6 kg).

The wide coverage loudspeaker model shall be the Meyer Sound ULTRA-X40 and the controlled coverage loudspeaker model shall be the Meyer Sound ULTRA-X42.